

Gauge on left shown with optional bumpers and handle, gauge on right shown in standard benchmount cabinet with rubber feet.

**3 Popular Ranges**

- 0.01 to 50 Torr Pirani Gauges
- 1 to 1500 Torr Diaphragm
- 30 Inches Hg to 150 PSIG

**Standard Features**

- NW-16, 1/8" NPT or Conflat® Flanges
- Bright, Easy to Read Green LED Display
- Bench Mount Cabinet with Rubber Feet
- Bracket Included For 1/8 DIN Panel Mount

**.01 to 50 Torr Digital Pirani Gauge**

**1 to 1500 Torr Digital Diaphragm Gauge**

**30 Inches Hg to 150 PSIG Digital Diaphragm Gauge**

*Buy Now! Go to [www.vacuumresearch.com](http://www.vacuumresearch.com) to order online*

Benchmount cabinet with rubber feet. Clip for mounting in 1/8 DIN panel cutout included. Sensor cable 10 ft (3m) long. Gauge operates from 15 to 24 VDC less than 200 mA. An external wall mount supply is included with each instrument. 90 to 240V. 50/60 Hz input and 15 VDC output.

3.5" Wide X 7.4" F to B X 1.84" H.  
90 mm W X 188 mm F-B X 46 mm H.  
Sensor not included.  
P/N: 902142 .....\$402.

Sensor, 1/8" NPT, all wetted parts stainless steel.  
P/N: 912011 .....\$86.

Sensor NW-16, all wetted parts stainless steel. P/N: 912072 .....\$126.

Sensor 1.33" OD Conflat®, non-rotatable, all wetted parts stainless steel.  
P/N: 912073 .....\$126.

Sensor VCR-4 FEM, all wetted parts stainless steel. P/N: 912074 .....\$159.

Benchmount cabinet with rubber feet. Clip for mounting in 1/8 DIN panel cutout included. Sensor cable 10 ft (3m) long. Gauge operates from 15 to 24 VDC less than 200 mA. An external wall mount supply is included with each instrument. 90 to 240V. 50/60 Hz input and 15 VDC output.

3.5" Wide X 7.4" F to B X 1.84" H.  
90 mm W X 188 mm F-B X 46 mm H.  
Sensor not included.  
P/N: 902143 .....\$431.

Sensor 1/8" NPT, Silicon Diaphragm P/N: 912091 .....\$251.

Sensor NW-16, Silicon Diaphragm P/N: 912023 .....\$290.

Sensor with 1.33" OD Conflat® flange, non-rotatable, and Silicon Diaphragm. P/N: 912026 .....\$290.

Sensor with Stainless Steel Diaphragm 1/4" NPT P/N: 912022 .....\$392.

See page 7 for more flange options.


Benchmount cabinet with rubber feet. Clip for mounting in 1/8 DIN panel cutout included. Sensor cable 10 ft (3m) long. Gauge operates from 15 to 24 VDC less than 200 mA. An external wall mount supply is included with each instrument. 90 to 240V. 50/60 Hz input and 15 VDC output.

3.5" Wide X 7.4" F to B X 1.84" H. 90 mm W X 188 mm F-B X 46 mm H. Sensor not included.  
P/N: 902144 .....\$458.

Sensor 1/8" NPT, Silicon Diaphragm P/N: 912149 .....\$251.

**All Stainless Steel Gauge Tubes For Outdoor Applications or Wherever The Use Of 304 SS Is Appropriate.**

All wetted parts as well as all external parts and connector pins are 304 SS. 1/8 in. NPT, NW-16, Conflat®, VCR-4 and special flanges can be provided. Add "SS" suffix to any tube P/N and to standard tube price: .....add \$43.



**3 & 5 Position Vacuum Gauges**

**Ordering Information**

Vacuum gauge & switch built into a 1/4 DIN enclosure suitable for bench or panel mounting. Standard sensor cables are each 10 ft. long. Cables up to 500 feet are available.

.01 to 50 Torr, 5 Position P/N: 902255 .. \$676.  
.01 to 50 Torr, 3 Position P/N: 902267 .. \$622.

1 to 1500 Torr, 5 Position P/N: 902256 .. \$698.  
1 to 1500 Torr, 3 Position P/N: 902268 .. \$643.

30" Hg to 150 PSIG, 5 Pos. P/N: 902257 \$780.  
30" Hg to 150 PSIG, 3 Pos. P/N: 902269 \$725.

Urethane bumpers, pair,  
P/N: V805001 .....\$43.

Carry handle installed on instrument,  
P/N: V805005 .....\$17.

**Power Supplies for all 3 Ranges**

90 to 240 V, 50/60 Hz power supply with 15 VDC, 200 mA output included with each new instrument. For spares orders P/N: V104124 .....\$52.

**Power Supplies for instruments shipped in 2005 and before.**

115 V 50/60 Hz input, 12 VAC @ 800 mA output. P/N: V104098 ... \$13.  
220 V 50/60 Hz input, 12 VAC @ 800 mA output. P/N: V104123 .....\$71.